



Rivet Bush Standoffs

Part No.	Thread	Hole Size+0.5-0	Sheet Thickness	Sheet Gauge	O/D E +/- 0.13	Body T+/-0.13	Skirt C/+0-0.13
M25??SH	M2.5	5.54	0.7/4.0	22-08SWG	7.92	AS REQUIRED	5.54
M3??RSH	M3	5.54	0.7/4.0	22-08SWG	7.92	AS REQUIRED	5.54
M35??RSH	M3.5	6.73	0.7/4.0	22-08SWG	9.52	AS REQUIRED	6.73
M4??RSH	M4	6.73	0.7/4.0	22-08SWG	9.52	AS REQUIRED	6.73
M5??RSH	M5	7.92	0.7/4.0	22-08SWG	11.10	AS REQUIRED	7.92
M6??RSH	M6	9.52	0.7/4.0	22-08SWG	12.70	AS REQUIRED	9.52
M8??RSH	M8	12.70	0.7/4.0	22-08SWG	15.87	AS REQUIRED	12.70
M10??RSH	M10	15.87	0.7/4.0	22-08SWG	19.05	AS REQUIRED	15.87
M12??RSH	M12	19.05	0.7/4.0	22-08SWG	25.40	AS REQUIRED	19.05

Round Rivet Bush Standoffs work the same as the 30101 series but have longer bodies for mounting components at a specific distance from the panel. The spigot is placed through a pre-punched hole and riveted on the reverse side, the serrations under the head provide excellent torque resistance. Various spigot lengths are available for different sheet thicknesses.

Materials & Finishes:-Steel Self Colour (Code 2)Steel Trivalent Zinc (Code 26)303 Stainless Steel (Code SS)

To Specify Use: Series No/Part No/Gauge/Length/Finish Code (eg 30105 M32010RSH26)THESE PARTS ARE SPECIAL ORDER SUBJECT TO MOQ

All information is given for guidance only and designers should satisfy themselves as to the suitability of the specification by requesting samples