




Series: 11512 Type: - DIN 7500



Tap-Tight Torx Cap Head

Part No.	Thread	D1	K	C	Recess
11512 M4**	M4	7.00	4.00	4.08	T20
11512 M5**	M5	8.50	5.00	5.09	T25
11512 M6**	M6	10.00	6.00	6.10	T30
11512 M8**	M8	13.00	8.00	8.13	T40
11512 M10**	M10	16.00	10.00	10.15	T50

Legend	
*	Usually Available from Stock
**	Non-preferred (Possible Lead Times)
***	Special Order Only


Thread / Length	5	6	8	10	12	16	20	25	30
M4	***	***	***	*	*	*	*	***	***
M5	***	***	***	***	***	***	***	*	***
M6	***	***	***	***	*	*	*	*	*
M8	***	***	***	***	***	***	***	***	***
M10	***	***	***	***	***	***	***	***	***

Thread forming screws have a trilobular thread form. These require a low level of assembly torque to initiate thread forming in sheet metal, castings and alloys. Further benefits: Screws form a female thread capable of accepting a standard metric machine screw should the need arise. The three lobed thread design allows the displaced parent material to cold flow into the relief areas of the screw thereby increasing the resistance to vibration and loosening of the screw.

Material: Steel Finish: Zinc Plated



Continued from previous page...



For the part number replace ** with the desired length found in the tables below:

All information is given for guidance only and designers should satisfy themselves as to the suitability of the specification by requesting samples