



## Rivet Nut Flat Head Round Body

Part No	Thread M	Grip Range	Hole Size	D1	D2	K	L
FR03-1	M3	0.5-2.0	5.0	4.9	8.0	0.8	10.0
FR04-1	M4	0.5-2.5	6.0	5.9	9.0	1.0	11.6
FR04-2	M4	3.0-5.5	6.0	5.9	9.0	1.0	14.0
FR05-1	M5	0.5-2.5	7.0	6.9	10.0	1.0	13.0
FR05-2	M5	3.0-5.5	7.0	6.9	10.0	1.0	16.0
FR06-1	M6	0.5-3.0	9.0	8.9	12.5	1.5	16.0
FR06-2	M6	3.0-5.5	9.0	8.9	12.3	1.3	19.5
FR08-1	M8	0.7-3.0	11.0	10.9	16.0	1.5	18.5
FR08-2	M8	3.0-5.5	11.0	10.9	16.0	1.5	21.0
FR10-1	M10	1.0-3.5	13.0	11.9	16.0	2.0	19.0
FR10-2	M10	2.4-4.0	13.0	12.9	19.0	2.0	21.0
FR10-3	M10	3.5-6.0	13.0	12.9	19.0	2.0	23.5
FR12-1	M12	1.0-4.0	16.0	15.9	22.0	2.1	28.0

Flat Head Rivet Nuts have a large flange to improve pull out resistance when under heavy loads. The knurled body provides extra torque resistance.

Materials and Finishes (Code):  
 Steel, Trivalent Zinc (60)

**All information is given for guidance only and designers should satisfy themselves as to the suitability of the specification by requesting samples**